MorphoAccess[®] SIGMA Lite Series By IDEMIA



Slim and powerful fingerprint access terminals





World's #1 fingerprint technology inside

1:10,000 user identification in 1 second

High capacity

30,000 templates, 250,000 IDs in authorized user list, 1 Million logs

Flexibility

Prox®, iClass® or MIFARE®/DESFire®/ NFC contactless card reader as an option



Anti-fraud features

Fake finger detection, duress finger, timed anti-pass back

Tough design IP65 rated and vandal resistant (IKO8)

MA SIGMA Lite

With blue/green/red LED

indicator and buzzer

Morpho

The SIGMA family welcomes new members!

Engineered with the same attention to detail and performance as their predecessor, the MorphoAccess® SIGMA Lite terminals by IDEMIA are specifically designed to equip narrow mounting surfaces, such as glass/ aluminum door mullions, turnstiles, or server rack doors.

With two designs and multiple card reader options, there are a variety of models to address the widest range of deployment scenarios, both indoors and outdoors.

World's #1 fingerprint technology inside

- Morpho fingerprint technology ranked #1 by NIST for accuracy
- Up to 10,000 users (30,000 templates) in 1:N identification mode
- 1:10,000 user matching in 1 second
- Accuracy maintained regardless of number of users in database
- FBI PIV IQS certified optical sensor

Full set of card reader options

- Prox®
- iClass®
- MIFARE®/MIFARE® Plus/DESFire®/NFC⁽¹⁾

Built for the real World

TOUGH DESIGN⁽²⁾



EASY INSTALLATION AND MAINTENANCE



 $^{(1)}$ NFC support depends on the smartphone model used with the MA SIGMA Lite/Lite+ device $^{(2)}$ IK08 rating is not available for MA SIGMA Lite+ design

COMPATIBLE WITH EXISTING INSTALLATIONS

(+)

Adjustable

or to either side of axis 60 mn



- Using MorphoManager by IDEMIA or MIK SDK on a Morpho network
- Using SecureAdmin application or SecureSDK on a Bioscrypt network

MORPHOACCESS® SIGMA LITE SERIES BY IDEMIA



Mozilla Firefox, Safari,

Internet Explorer)

⁽³⁾ Alternate password solution instead of fingerprints ⁽⁴⁾ Prevents repeated authorizations by the same user, within a configurable time period

smartphone)

Windows)

configuration and

transaction log retrieval

Technical specifications

- CPU: ARM[®] Cortex[™]-A9 core 1GHz
- Linux Operating System
- FBI PIV IQS certified optical fingerprint sensor
- Contactless reader options: Prox®, iClass®, MIFARE®/MIFARE® Plus/ DESFire®/NFC⁽¹⁾
- Network/Communication:
 - Ethernet, RS485, USB
 - Wi-Fi option
- Power supply:
- 12V-24V DC
- Power over Ethernet (PoE), compatible with PoE+ switches

- Internal storage capacity: 512MB Flash, 512MB RAM
 - 500 user records, extendable to 3,000 or 10,000 with license (*3 templates each, including 1 duress)
 - 250,000 IDs in authorized user list - 1 Million transaction logs
 - I Million transaction logs
- Inputs/outputs: Wiegand In & Out (customizable up to 512 bits), OSDP, Door Relay, 2 General Purpose Inputs (including Door monitoring), 2 General Purpose Outputs
- Tamper switches

• Operating conditions:

- Temperature: -20°C to 55°C (-4°F to 131°F)
- Humidity: 10% to 80% (non condensing)
- Ingress protection: IP65
- Mechanical impact protection: IKO8(2)
- HxWxD = 156*68*62 mm (6.14*2.68*2.44 inches)
- Weight: 280 grams
- EMC/Safety standards:
 - CE, CB, FCC, BIS
 - UL294 (for indoor use only)
- RoHS, REACh and WEEE compliant



THE SIGMA FAMILY

 $^{(1)}$ NFC support depends on the smartphone model used with the MA SIGMA Lite/Lite+ device $^{(2)}$ IK08 rating is not available for MA SIGMA Lite+ design



All rights reserved. Specifications and information subject to change without notice. The products described in this document are subject to continuous development and improvement. All trademarks and service marks referred to herein, whether registered or not in specific countries, are the property of their respective owners.

