

ELYCTIS

e-ID expert

ID READER - Desktop series *Citizen Home ID authentication*



- Reads any eID chip
- Contact and contactless
- Fast reading time
- Reduced size
- Easy branding personalization
- Ideal for mass market home ID

www.elyctis.com

ID READER - Desktop series

Features

General

- Dimensions 80 x 65 x 12,5 mm for ID READER 112
96 x 65 x 13,8 mm for ID READER 111 & 121
- Temperature In operation: -20°C to +50°C
Storage: -40°C to +80°C
- Communication USB 2.0 full speed (12 Mbps)
- Host operating systems Windows, MacOS, Linux, Android

Contactless reader

- Supported protocols ISO 14443 Part 1 to 4, type A/B – T=CL and Mifare
All Mifare products: Ultralight, 1K, 4K, Plus, DESFire EV1, Smart MX,...
- Speed Baudrate up to 848 kbps
- Communication CCID compliant (Windows, MacOS, Linux)
Custom CCID library (Android)
PC/SC 2.01 compliant (Windows, MacOS, Linux)
PC/SC .net wrapper (Windows)
- Firmware Support for RF configuration
Pass-through command to reach protocol lower layer
Field upgradable

Contact card reader

- Supported protocols ISO 7816 – T=0 and T=1
5V, 3V, 1.8V, ISO 7816 Class A/B/C
- Speed Baudrate up to 230 kbps
Clock: Up to 10 Mhz
- Communication CCID compliant (Windows, MacOS, Linux)
Custom CCID library (Android)
PC/SC 2.01 compliant (Windows, MacOS, Linux)
PC/SC .net wrapper (Windows)
- Firmware Field upgradable

Product Range

	ID READER 111	ID READER 112	ID READER 121
Contactless reader		✓	✓
Contact reader	✓		✓



ELYCTIS sas

91 rue Benjamin Franklin – 84120 Pertuis – FRANCE
Tel. +33 6 27 71 37 68
contact@elyctis.com - www.elyctis.com
Siret 508 994 449 00033 – VAT number FR47 508 994 449

ELYCTIS HK Limited

D2 2/F Mai Wah Ind. Bldg. – 1-7 Wah Sing St. Kwai Chung
NT – HONG KONG
Tel. +852 91 08 78 58
contact_hongkong@elyctis.com