


ELYCTIS

e-ID expert

ID READER - OEM series

Multipurpose RFID reader



- Fast reading time
- Ideal for mass market
- Type A (incl. Mifare) & type B
- Field upgradable FW
- Low power (LPCD)

www.elyctis.com

ID READER

Applications

- Car sharing
- Vending
- Access control
- Tracability
- Gambling

Product Range

ID READER 012 RS232	
Contactless	✓

Features

General

- Dimensions 40 x 60 x 7 mm
- Temperature In operation: -20°C to +70°C
Storage: -40°C to +80°C
- Communication RS232 (Default 38400 Bauds)
- Host OS Any Embedded hosts

Contactless interface

- Supported protocols ISO 14443 Part 1 to 4, type A/B – T=CL and Mifare
All Mifare products: UltraLight, Ultralight C, 1K, 4K, Plus, DESFire
- Communication A proprietary PC/SC like protocol through RS232
- Firmware Support for RF configuration
Pass-through command to reach protocol lower layer
Field upgradable
- Standby mode LPCD Mode (Low Power Card Detection) - Card presence
detection.
Low consumption (150µA)
- Normal mode Consumption (50mA)

ELYCTIS sarl

91 rue Benjamin Franklin – 84120 Pertuis – FRANCE
Tel. +33 6 27 71 37 68

contact@elyctis.com - www.elyctis.com

Siret 508 994 449 00033 – VAT number FR47 508 994 449

ELYCTIS HK Limited

D2 2/F Mai Wah Ind. Bldg. – 1-7 Wah Sing St. Kwai Chung
NT – HONG KONG

Tel. +852 91 08 78 58

contact_hongkong@elyctis.com