

Pocketable and powerful, XM75+ is Janam's next-generation rugged mobile computer for input-intensive applications. Offering the same versatility and flexibility as Janam's XM75, XM75+ delivers more features and greater performance to optimize workflows. With a 4.3-inch touch screen and backlit numeric keypad, XM75+ is one of the only devices specially designed for mobile workers that prefer keypad and touch screen functionality in the same device.

XM75+ supports Android 11 with Google Mobile Services (GMS) and provides the latest technological advancements to help transportation, logistics, field service and delivery companies boost productivity, streamline operations and improve the customer experience. A blazing-fast Snapdragon octa-core processor enables longer battery life, advanced graphics and robust voice and data communications.

Backward compatibility with XM75 accessories allows Janam's global customer base to reuse existing technology while cost-effectively upgrading to the latest mobile computing platform.





















8MP REAR-FACING CAMERA



AND NFC













## **XM75+ Specifications**

| TECHNICAL        |   |
|------------------|---|
| Operating System | Android 11  |
| Processor        | 1.8 GHz Qualcomm Snapdragon™ octa-core  |
| Memory           | 3GB/32GB  |
| Expansion        | User-accessible microSD card slot witih support up to 512GB using ExFAT file system |
| Power            | 4200mAh 3.85v rechargeable<br>Li-ion battery  |

| PHYSICAL    |  |
|-------------|--|
| Dimension   | 3.02" x 6.53" x 1.15"<br>76.83 mm x 166.01 mm x 29.27 mm |
| Weight      | 10.5oz / 300g including battery                          |
| Display     | 4.3" WVGA (480 x 800 pixel) with Corning Gorilla Glass 3 |
| Touch Panel | Capacitive touch screen                                  |

| ENVIRONMENTAL                  |   |
|--------------------------------|---|
| Operating Temperature          | -4º to 140º F / -20º to 60º C   |
| Storage Temperature            | -13° to 158° F / -25° to 70° C  |
| Humidity                       | Non-condensing, 95%   |
| Drop                           | Multiple 5ft / 1.5m drops to concrete on all sides across a wide temperature range per MIL-STD 810G |
| Water & Dust                   | IP67  |
| Electro Static Discharge (ESD) | +/- 15kV air; +/- 8kV contact   |

| INTERFACE FEATURES |   |
|--------------------|---|
| Audio              | 3.5mm headset jack; speaker; two microphones                                    |
| Alerts             | Vibration; LED indicators   |
| LED Indicators     | Dual-color  |
| Motion Sensor      | Gyroscope; Accelerometer;<br>Light Sensor; Proximity<br>Sensor; Digital Compass |
| External Buttons   | Numeric keypad (24 keys) with backlight;<br>2 external buttons                  |

| DATA CAPTURE                 |   |
|------------------------------|---|
| Imager                       | Honeywell N3601SR 2D Imager   |
| Camera                       | 8MP color rear-facing<br>autofocus camera with<br>user-controllable LED flash   |
| RFID/NFC (WWAN version only) | Reads ISO14443A/ISO14443B/ISO15693;<br>MIFARE UltraLight; MIFARE 1k/4k/DESFire;<br>MIFARE DESFire EV1; Sony FeliCA;<br>NFC Tag Types 1 to 5 |

| NETWORK COMMUNICATION |   |
|-----------------------|---|
| USB                   | MicroUSB port supports USB 2.0 High-Speed   |
| WWAN                  | EDGE/GPRS/GSM: 900/1800<br>WCDMA: B1/2/5/6/8/19<br>LTE FDD: B1/2/3/5/7/8/17/20<br>LTE TDD: B40/41   |
| WLAN                  | 802.11a/b/g/n/ac/ax (ready)/d/h/i/k/r/v,<br>1x1 MU-MIMO   |
| Security              | WEP (40 or 104bit); WPA/WPA2 Personal (TKIP, AE WPA/WPA2 Enterprise (TKIP/AES) - WPA3 Personal(SAE), WPA3 Enterprise(AES) WPA3 Enterprise 192-bit mode(GCMP 256) Enhanced Open(OWE); PEAP (MSCHAPv2, GTC), TLS, TTLS (PAP, MSCHAP, MSCHAPv2, GTC) PWD, SIM, AKA, AKA', LEAP |
| WPAN                  | Bluetooth Class I, v5.1, BLE support  |
| GPS                   | Qualcomm GPS supports GLONASS and Beidou  |

| ACCESSORIES                |                                 |
|----------------------------|---------------------------------|
| Single-Slot USB Cradle Kit | Single-Slot Ethernet Cradle Kit |
| Four-Slot Cradle Kit       | Four-Slot Battery Charging Kit  |
| Power Adapter              | Spare Battery                   |
| Nylon Holster              | Operating Case                  |
| Stylus with Tether         | Handstrap                       |
| Trigger Handle             |                                 |

| SAFETY / REGULATORY |   |
|---------------------|---|
| Safety              | IEC/EN-60950-1, cUL 60950-1, UN38.3, UL2054/<br>UL1642, IEC62133, KC, PSE |
| Radio               | FCC, CE (EMC, RF, SAR, RED), IC   |
| Environmental       | RoHS, WEEE Compliant, NRCAN   |



**Janam Technologies** 100 Crossways Park West Suite 105 Woodbury, NY 11797 Phone: +1.877.JANAM.99 Local: +1.516.677.9500 Fax: +1.516.320.8031 Email: inquiries@janam.com Contact Technical Support: NA: +1.866.915.5311 EMEA: +44.1202.946945 Email: janamcare@janam.com