



# ELYPSO

## Card printer specification

### STANDARD PRINTER FEATURES

#### Printer design:

- Compact printer for front-desk environment
- LED control panel

#### Print technology:

- Direct-to-card
- Dye-sublimation/resin thermal transfer

#### Print capability:

- One- or two-sided printing, edge-to-edge

#### Print resolution:

- 16 million colors
- Standard mode: 300x300 dpi (dots per inch)  
*For standard monochrome and color printing*
- Extended mode: 300x600 dpi (dots per inch)  
*For enhanced monochrome and color printing*
- Extended mode: 300x1200 dpi (dots per inch)  
*For enhanced monochrome printing*

#### Printing performance:

- Color YMCKO: 20.2 s/card
- Color YMCKO-K: 27.3 s/card
- Monochrome: 6.5 s/card

#### Printer memory:

- 32 MB (RAM) standard, optional 64 MB<sup>1</sup>

#### Interfaces:

- USB (1.0, 1.1, 2.0, 3.0)
- Ethernet TCP-IP, 10BaseT, 100BaseT (Traffic Led)

#### Safety:

- Support for Kensington® security lock
- Data encryption for magnetic encoding

#### User-friendly operation:

- Full front operation
- Graphical notifications from the printer<sup>2</sup>; cleaning alerts, empty/low level ribbon alerts, etc.
- Easy to reach on/off button
- Easy to access technical parts thanks to side
- Drop-in cassette with easy handling
- Operator replaceable print head

#### Warranty:

- 1-year warranty on printer<sup>4</sup>
- 1-year warranty on original print head (unlimited passes)<sup>4</sup>

### OPTIONAL PRINTER FEATURES

- On-site dual-sided printing activation by a RFID
- Reject tray: 30 cards (0.76 mm - 30 mil)
- Wireless range: wireless connection 802.11 b/g
- Color LCD touch-screen
- Warranty extension program

### ENCODING OPTIONS

- Magnetic stripe encoder ISO 7811, track 1, 2 and 3 high and low coercivity, stripe down (0,76mm - 30mil cards only)
- Magnetic stripe encoder JIS Type II
- ISO 7813 smart card contact station for 3rd party external contact encoder
- Contact smart encoder - PC/SC, EMV 2000-1
- Contactless ISO 14443A, B, ISO 15693, MIFARE, DESfire, HID iCLASS, UHF encoder: ETSI (EN or FCC (part 15.247) standard compliance: EPC C1 Gen2 / ISO18000-6C
- Other specific encoders upon request
- Internal USB or IP ports
- Options can be combined
- Factory-installed or installed on-site

### SOFTWARE

#### Delivered with cardPresso XXS Lite for designing and editing badges:

- Internal database up to 50 records
- Signature acquisition (compatible with Evolis Sig100 Sig200 and SigActiv signature pads)
- User interfaces available in 28 languages
- Compatible with Windows® 10, 8, 7, Vista (32/64-bit), Windows Server 2008, Windows Server 2012, Windows Server 2016, Windows Server 2019 and Mac OS (64-bit Processor only) from 10.7 onwards.

#### Delivered with Evolis Premium Suite® for Windows®:

- Printer driver (Windows certification)
- Evolis Print Center for administration and settings
- Evolis Printer Manager for graphical notification<sup>3</sup>
- User interface languages available: English, French, Spanish, German, Italian, Portuguese (Brazil), Dutch, Simplified Chinese, Traditional Chinese, Japanese, Korean, Russian, Polish, Turkish, Farsi
- Compatible with Windows® 10, 8, 7 (32/64-bit), Windows Server 2008 R2 (64 bits only), Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 (32/64-bit).

#### Delivered with a driver for Mac OS (from 10.11 onwards)

#### Linux upon request (RPM installation packages & DEB installation packages)

#### Detailed OS driver compatibility available on [www.evolis.com](http://www.evolis.com)

#### Evolis Premium SDK available for remote supervision of the printer, while facilitating and speeding up integration into IT systems

### PRINTER RIBBON SPECIFICATIONS

#### The Elypso is designed to work only with Evolis High Trust® ribbons.

To maximize the quality and durability of printed cards the lifespan of the print head and the overall printer reliability, use Evolis High Trust® ribbons.

- Automatic ribbon identification and setting
- Delivered in a drop-in cassette for intuitive installation and easy handling
- Ribbon saver for monochrome printing
- Recyclable supply cores and cassette
- Recycled packaging

#### Ribbon capacity:

- YMCKO: 300 prints/roll
- YMCKO-K: 200 prints/roll (dual-sided)
- 1/2 YMCKO: 400 prints/roll
- 1/2 YMCKO-KO: 250 prints/roll (dual-sided)
- KO: 600 prints/roll
- SO-KO: 250 prints/roll (dual-sided)
- Black monochrome ribbon: 2000 prints/roll
- BlackFLEXmonochrome ribbon: 1000 prints/roll
- Blue P300C monochrome ribbon: 1000 prints/roll
- Red P186C monochrome ribbon: 1000 prints/roll
- Green P356C monochrome ribbon: 1000 prints/roll
- White monochrome ribbon: 1000 prints/roll
- Metallic silver monochrome ribbon: 1000 prints/roll
- Metallic gold monochrome ribbon: 1000 prints/roll
- Signature panel monochrome ribbon: 1000
- Scratch-off monochrome ribbon: 1000 prints/roll
- Hologram varnish ribbon: 400 prints/roll
- Y=Yellow, M=Magenta, C=Cyan, K=Black Resin
- O=Overlay, S=Silver

### CARD SPECIFICATIONS

- Manual feeder: card to card printing
- Card thickness: 0.50 to 1.25 mm (20 to 50 mil)

#### No gauge adjustment

Case by case for 0.25 mm (10 mil) only for monochrome printing

#### Card types accepted:

- ISO 7810 format, Type ID 1, CR-80 size
- 85.6 x 53.98 mm (3.370" x 2.125")
- PVC, Composite PVC, PET
- ABS<sup>1</sup>, special varnished cards<sup>1</sup>

### PRINTER SPECIFICATIONS

#### Physical dimensions (H x W x D):

- 195 x 205 x 314 mm (7.68" x 8.07" x 12.36")
- With reject tray:
- 195 x 205 x 415 mm (7.68" x 8.07" x 16.34")

#### Weight:

- 2.95 kg (6.5 lbs)

#### Electronic requirements:

- Power supply: 100-240 Volts AC, 50-60 Hz, 1.7 A
- Printer: 24 Volts DC, 2.71 A

### OPERATING ENVIRONMENT

- Min / Max operating temperature: 15° / 30° C (59° / 86° F)
- Humidity: 20% to 65% non-condensing
- Min / Max storage temperature: -5° / +70° C (23° / 158° F)
- Storage humidity: 20% to 70% non-condensing
- Operating ventilation: free air

### SOUND

(evaluated according to the ISO 7779 standard)

Sound pressure in assistant positions LpAm (color mode YMCKO):

- When operating: 48 dB (A)
- In sleep mode: background noise level

### CERTIFICATIONS / COMPLIANCES

- Standby, sleep modes & reduced energy consumption
- Recyclable enclosure plastics
- CE, FCC, ICES, VCCI, CCC, KC, BIS, EAC
- RoHS
- Recyclable packaging

### INCLUDED WITH THE PRINTER

- CD with drivers and user's manuals
- Quick Start Guide
- Warranty booklet
- Starter cleaning kit
- USB cable (1.80m)
- Power supply
- Power cord (region specific)

<sup>1</sup> Under specific conditions / <sup>2</sup> Depends on the Windows® version / <sup>3</sup> Requires the.net 4.0 client profile version

<sup>4</sup> Warranty subject to observance of specific conditions and use of Evolis High Trust® ribbons