



## iClock700

### Fingerprint Time & Attendance and Access Control Terminal

iClock700 is a 3.5-inch TFT screen Time & Attendance and Access Control Terminal. With the new user-friendly firmware, iClock700 is equipped with features like stunning GUI, more stability, faster matching speed and better expandability.

iClock700 is compatible with various types of USB flash disks, ADMS and former SDK. Moreover, TCP/IP and USB client ensures a smooth data transmission between device and PC. It also has Wi-Fi and 3G/4G connectivity and access control connectivity with Wiegand out and in, electric lock, door sensor, exit button, alarm and door bell.

---

## Features

### Remarkable User Experience

- Intuitive and stunning UI designed with the most popular and internationalized element.
- Interface operation adopts modularized hierarchical design. Simpler, Better and More logical.
- Faster matching speed: Less than 1 second.

### Enhanced Features and Performance

- Multi-languages.
- Data backup and retrieval.

- Advanced User ID consisting of letters and numbers.
- Chip encryption for firmware protection.

### Excellent Expandability

- Easy to extend functions and customize customers' requirements.

### Access Control Interface


- For Wiegand in and out, door lock connection, alarm and bell.

# Specifications

<b>Fingerprint Capacity</b>	8,000 (Optional: 40,000)
<b>Card Capacity</b>	10,000 (Optional: 40,000)
<b>Record Capacity</b>	200,000
<b>Display</b>	3.5-inch TFT Screen
<b>Communication</b>	TCP/IP, RS485/RS232*, USB-host / USB-Client (optional)
<b>Standard Functions</b>	Workcode, SMS, DST, Webserver, Schedule Bell, 9-digit User ID, Self-Service Query, Automatic Status Switch, Photo ID, T9 Input, Anti-passback, Camera, Built-in Battery
<b>Access Control Interface</b>	3rd Party Electric Lock, Door Sensor, Exit Button, Alarm, Door Bell
<b>Wiegand Signal</b>	Input & Output
<b>Optional Functions</b>	ID / IC / HID Card, External Printer, ADMS, Wi-Fi, 4G, Multiple Verify Modes, Https
<b>Software</b>	ZKBioTime.Net / ZKBio Time
<b>Power Supply</b>	DC 12V 3A
<b>Verification Speed</b>	≤ 1 Sec.
<b>Operating Temp.</b>	0°C - 45°C
<b>Operating Humidity</b>	20% - 80%
<b>Dimension</b>	225.2*166.0*46.3mm (Length*Width*Thickness)
<b>Gross Weight</b>	1.94 kg

\* Note: RS232 is for external printer and RS485 is for RS485 readers.

## Configuration



## What's in the Box

