

# iCLASS SE® U90 Long Range Reader


## UHF LONG RANGE READER FOR SECURE PARKING AND GATE CONTROL



HID's iCLASS SE® U90 Long Range Readers offer an extended range solution for parking and gate control. Featuring advanced encryption technology, the solution delivers secure ultra high frequency (UHF) access control. With a read range of up to five meters, the iCLASS SE U90 can read multiple credential types and support a mixed credential population. The ability to combine building access with parking and gate control on a single card offers both convenience and security.

As part of HID's iCLASS SE platform for enhanced security, the readers utilize advanced authentication through the platform's Secure Identity Object (SIO) data model. . . to help prevent unauthorized access. When paired with SIO-enabled UHF credentials, the platform provides trusted and secure communication between the card and reader to prevent unauthorized access.

Built to withstand exposure to severe weather, the reader includes a rugged housing that protects the antennae and electronics from harsh conditions. The easy-to-install readers are built on the VESA standard and do not require custom mounting hardware. Once installed, the iCLASS SE U90 can be locally configured via an Ethernet port and a user-friendly web interface for ease of maintenance.




### **BENEFITS:**

- Convenient – Discreet hands-free authentication solution for long range parking and gate control.
- Dynamic – Field configurable via a full user interface for ease of maintenance.
- Compliant - Supports UHF ISO 18000-6C compliant

### **TECHNICAL HIGHLIGHTS:**

- Proven technology offers consistent read range.
- Open architecture design enables use of standard or custom keys for enhanced security.
- IP65 rating allows outdoor mounting in extreme environments.
- Supports Wiegand standards.

# iCLASS SE® U90 Long Range Reader



## TECHNOLOGY FEATURES:

- Dual payload – SIO® and EPC (Electronic Product Code) data payload for backward interoperability.
- Multi-Layered Security (beyond the chip security) - Supports data authenticity and privacy through HID's SIO supporting advanced cryptography.
- SIO data binding – Inhibits data cloning by binding an object to a specific credential.
- Easy configuration with the embedded web interface - Provides all tools necessary for a seamless installation.

## iCLASS SE U90 Long Range Reader

<b>Base Model Number</b>	RDRSEU90		
	<b>ELECTRONIC</b>		
<b>Transmit Frequency</b>	865 - 868 MHz / 902 - 928 MHz dependent on regional regulations		
<b>Typical Maximum Read Range</b>	Up to 5 meters - depends on Installation conditions and vehicle windshield specification <sup>4</sup>		
<b>Input Voltage (VDC)</b>	12VDC or 24VDC		
<b>Current</b>	Standby Avg <sup>1</sup> 320mA @ 12VDC / 160mA @ 24VDC	Max AVG <sup>2</sup> 400mA @ 12VDC 200mA @ 24VDC	PEAK <sup>3</sup> 1.0A @ 12VDC 0.5A @ 24VDC
<b>Cable Length</b>	Wiegand = 500 ft (152 m) – 22 AWG; 300 ft (91 m) – 24 AWG		
	<b>PHYSICAL</b>		
<b>Dimensions</b>	9.10" x 9.10" x 2.75" (23.1 cm x 23.1 cm x 7.0 cm)		
<b>Color</b>	Black		
<b>Housing Method</b>	UL94 Polycarbonate		
<b>Mounting</b>	Drill mounting box to meet application. Drill points provided for US and EU wall boxes and 75 mm, 100 mm, 200 mm VESA mounts.		
	<b>THERMAL</b>		
<b>Storage Temperature</b>	-67° to 185° F (-55° to 85° C)		
<b>Operating Temperature</b>	-30° to 150° F (-35° to 65° C)		
<b>Operating Humidity</b>	5% to 95% relative humidity non-condensing		
<b>Environmental Rating</b>	IP65		
	<b>OTHER</b>		
<b>Standards</b>	UL294/cUL (US & Canada), CB Scheme, FCC Certification (US), IC (Canada), CE (EU), IFETEL (Mexico), ANATEL (Brazil)		
<b>Crypto-Processor Hardware Common Criteria Rating</b>	EAL5+		
<b>Card Compatibility</b>	UHF EPC Class 1 Gen 2, ISO 18000-6C		

<sup>1</sup> Standby AVG - RMS current draw without a card in the RF field

<sup>2</sup> Maximum AVG - RMS current draw during continuous card reads. Not evaluated by UL

<sup>3</sup> Peak - highest instantaneous current draw during RF communications

<sup>4</sup> Vehicles with tinted or heated windshields may impact read range. Please consult the vehicle manual for compatibility with UHF and RF credentials, and PLT-01952 (iCLASS SE U90 User Guide) for reader installation and credential location.



hidglobal.com

North America: +1 512 776 9000 | Toll Free: 1 800 237 7769

Europe, Middle East, Africa: +353 91 506 900

Asia Pacific: +852 3160 9800 | Latin America: +52 55 9171 1108

**For more global phone numbers click here**

© 2024 HID Global Corporation/ASSA ABLOY AB. All rights reserved.

2024-05-03-pacs-iclass-se-u90-reader-ds-en PLT-02450

Part of ASSA ABLOY